


Spherical Roller Bearing

22300 Series-22311K



WUXI GUANGQIANG BEARING TRADE CO.,LTD

Обозначение	22311K
Основные размеры (мм)	
d	55
D	120
B	43
rs min	2
Номинальная грузоподъемность (кН)	
Динамический (Cr)	204
Статический (Cor)	234
Ограниченная скорость (об / мин)	
Смазка	2800
Масло	4400
Масса (кг)	2.25

Spherical roller bearings have two rows of rollers, a common sphered outer ring raceway and two inner ring raceways inclined at an angle to the bearing axis . The centre point of the sphere in the outer ring raceway is at the bearing axis. Therefore, these bearings are self-aligning and insensitive to misalignment of the shaft relative to the housing, which can be caused, for example, by shaft deflection. Spherical roller bearings are designed to accommodate heavy radial loads, as well as heavy axial loads in both directions.

Symmetrical rollers

Symmetrical rollers self-adjust, providing optimal load distribution along the roller length. This keeps stresses low under all load conditions and extends bearing service life.

Roller tolerances

The rollers in an spherical roller bearing are manufactured to extremely tight dimension and form tolerances. Each roller is practically identical in size and shape to the other rollers in the set. This optimizes load distribution over the rollers to maximize bearing service life.

Special roller profile

The roller profile determines the stress distribution in the roller/raceway contact area. The special profile distributes loads more evenly along the rollers and prevents stress peaks at the roller ends to extend bearing service life .

Self-guiding rollers and a floating guide ring between the two rows of rollers

Self-guiding rollers reduce friction and frictional heat. A floating guide ring guides unloaded rollers so that they enter the load zone in the optimal position.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com