

Single Row Tapered Roller Bearing

30200 Series-30218J2



WUXI GUANGQIANG BEARING TRADE CO.,LTD

Обозначение	30218J2
Основные размеры (мм)	
d1	90
D	160
B	32.5
Номинальная грузоподъемность (кН)	
dyc (Cr)	194
stc (Kop)	245
Пу	28.5
Номинальная скорость (об / мин)	
Рейтинги скорости	3000
Ограничение скорости	4000
Вес (кг)	2.55
ISO335	
Размеры (ABMA)	3FB
Размеры (мм)	
d	90
d1 □	118
B	30
C	26
r1,2 (мин)	2.5
r3,4 (мин)	2
a	31
Размеры абатмента и галтели (мм)	
да (макс)	104
дБ (мин)	101
Да (мин)	140
Да (макс.)	150
Дб (мин)	150
Са (мин)	5
Сb (мин)	6.5
ра (макс)	2
rb (макс.)	2
Ценить	
e	0.43
Y	1.4
Эй	0.8

GQZ high quality 30200 Series Single Row Tapered Roller Bearing

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly

and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com