

Single Row Tapered Roller Bearing

30200 Series-33020/Q



WUXI GUANGQIANG BEARING TRADE CO.,LTD

Обозначение	33020/Q
Основные размеры (мм)	
d1	100
D	150
B	39
Номинальная грузоподъемность (кН)	
dyc (Cr)	224
stc (Kop)	390
Пу	41.5
Номинальная скорость (об / мин)	
Рейтинги скорости	3000
Ограничение скорости	4000
Вес (кг)	2.40
ISO335	
Размеры (ABMA)	2CE
Размеры (мм)	
d	100
d1 □	122
B	39
C	32.5
r1,2 (мин)	2
r3,4 (мин)	1.5
a	29
Размеры абатмента и галтели (мм)	
да (макс)	109
дБ (мин)	108
Да (мин)	135
Да (макс.)	142
Дб (мин)	143
Са (мин)	7
Сb (мин)	6.5
ра (макс)	2
rb (макс.)	1.5
Ценить	
e	0.3
У	2
Эй	1.1

GQZ high quality 30200 Series Single Row Tapered Roller Bearing

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly

and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com