

Single Row Tapered Roller Bearing
 30300 Tapered Roller Bearing-30317J2

Обозначение	30317J2
Основные размеры (мм)	
d1	85
D	180
B	44.5
Номинальная грузоподъемность (кН)	
dyc (Cr)	303
stc (Cor)	365
Py	40.5
Номинальная скорость (об / мин)	
Рейтинги скорости	2800
Ограничение скорости	4000
Вес (кг)	4.85
ISO335	
Размеры (ABMA)	2GB
Размеры (мм)	
d	85
d1 □	126
B	41
C	34
r1,2 (мин)	4
r3,4 (мин)	3
a	35
Размеры абатмента и галтели (мм)	
да (макс)	107
дБ (мин)	99
Да (мин)	156
Да (макс.)	166
Дб (мин)	167
Ca (мин)	6
Cb (мин)	10.5
ра (макс)	3
rb (макс.)	2.5
Ценить	
e	0.35
Y	1.7
Эй	0.9

GQZ bearings wholesale high quality 30300 Single Row

Tapered Roller Bearing

The dimensions of 30303 tapered roller bearings are 17.000 mm inner diameter, 47.000 mm outer diameter and 15.250 mm thickness.

30300 series tapered roller bearings are characterized by high load carrying capacity, relatively small size and weight, compact radial structure, high machining accuracy and high surface hardness.

30303 tapered roller bearings features:

1□high load carrying capacity: despite its short cross-sectional diameter and relatively small size and weight, 30300 tapered roller bearings have high load carrying capacity and can withstand large radial and axial loads.

2□radial structure is compact: its internal diameter size and load capacity compared with other types of bearings, the outer diameter is small, especially suitable for radial mounting support structure size limitations.

3□High machining accuracy: The bearings are of high machining accuracy and high surface hardness, which can withstand several times more force than its bearing force, ensuring the safety of the use of bearings and stable performance.

In addition, 30300 tapered roller bearings are used in a wide range of applications, including but not limited to automobiles, new energy sources, crushers, machine tool spindles, mining mills, differentials, speed reducers, granulators, cranes, oilfields and so on. These bearings assume important roles in mechanical equipment such as transmitting power, bearing loads, reducing friction, etc. Their performance is directly related to the stability and service life of mechanical equipment.



Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-
Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com