

Single Row Tapered Roller Bearing
 31300 Tapered Roller Bearing-31319J2

Обозначение	31319J2
Основные размеры (мм)	
d1	95
D	200
B	49.5
Номинальная грузоподъемность (кН)	
dyc (Cr)	292
stc (Cor)	355
Py	39
Номинальная скорость (об / мин)	
Рейтинги скорости	2400
Ограничение скорости	3400
Вес (кг)	6.95
ISO335	
Размеры (ABMA)	7GB
Размеры (мм)	
d	95
d1 □	145
B	45
C	32
r1,2 (мин)	4
r3,4 (мин)	3
a	60
Размеры абатмента и галтели (мм)	
да (макс)	114
дБ (мин)	110
Да (мин)	157
Да (макс.)	186
Дб (мин)	187
Ca (мин)	5
Cb (мин)	17.5
ра (макс)	3
rb (макс.)	2.5
Ценить	
e	0.83
Y	0.72
Эй	0.4

GQZ bearings wholesale high quality 31300 Single Row

Tapered Roller Bearing

31303 tapered roller bearings, the inner diameter is 17mm, the outer diameter is 47mm and the width is 15.5mm.

31330 tapered roller bearings, the inner diameter is 150mm, an outer diameter is 320mm and a width is 75mm.

32300 series tapered roller bearings features:

31300 series tapered roller bearings are characterized by strong load carrying capacity, smooth operation and long service life, which are widely used in automobile, engineering machinery, metallurgical equipment, mining machinery and other fields.

31300 series tapered roller bearings belong to a kind of roller bearings, its inner and outer ring raceway cross-section is conical, mainly to bear radial load mainly radial and axial combined load, at the same time, can also withstand tilting moment. The design of this type of bearing enables it to provide stable support and load carrying capacity in various applications, thus ensuring stable operation and long-term use of the equipment.



Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-
Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com