

Single Row Tapered Roller Bearing

32300 Series-32314BJ2/QCL7C



WUXI GUANGQIANG BEARING TRADE CO.,LTD

Обозначение **32314BJ2/QCL7C**

Основные размеры (мм)

d1 70

D 150

B 54

Номинальная грузоподъемность (кН)

dyc (Cr) 325

stc (Cop) 400

Пу 46.5

Номинальная скорость (об / мин)

Рейтинги скорости 3400

Ограничение скорости 4300

Вес (кг) 4.25

ISO335

Размеры (ABMA) 5GD

Размеры (мм)

d 70

d1 □ 113

B 51

C 42

r1,2 (мин) **3**

r3,4 (мин) 2.5

a 44

Размеры абатмента и галтели (мм)

да (макс) 85

дБ (мин) 82

Да (мин) 115

Да (макс.) 138

Дб (мин) 141

Са (мин) **7**

Сb (мин) 12

ра (макс) 2.5

rb (макс.) **2**

Ценить

e 0.54

Y 1.1

Эй 0.6

GQZ high quality 32300 Series Single Row Tapered Roller Bearing

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered

roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com