

Single Row Tapered Roller Bearing

33000 Series-33016/Q



WUXI GUANGQIANG BEARING TRADE CO.,LTD

Обозначение	33016/Q
Основные размеры (мм)	
d1	80
D	125
B	36
Номинальная грузоподъемность (кН)	
dyc (Cr)	168
stc (Cop)	285
Пу	32
Номинальная скорость (об / мин)	
Рейтинги скорости	3600
Ограничение скорости	5000
Вес (кг)	1.65
ISO335	
Размеры (ABMA)	2CE
Размеры (мм)	
d	80
d1 □	102
B	36
C	29.5
r1,2 (мин)	1.5
r3,4 (мин)	1.5
a	26
Размеры абатмента и галтели (мм)	
да (макс)	90
дБ (мин)	87
Да (мин)	112
Да (макс.)	117
Дб (мин)	119
Са (мин)	6
Сb (мин)	6.5
ра (макс)	1.5
rb (макс.)	1.5
Ценить	
e	0.28
Y	2.1
Эй	1.1

GQZ high quality 33000 Series Single Row Tapered Roller Bearing

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered

roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com