


Single Row Tapered Roller Bearing

33000 Series-33021/Q



WUXI GUANGQIANG BEARING TRADE CO.,LTD

Обозначение	33021/Q
Основные размеры (мм)	
d1	105
D	160
B	43
Номинальная грузоподъемность (кН)	
dyc (Cr)	246
stc (Cор)	430
Пу	45.5
Номинальная скорость (об / мин)	
Рейтинги скорости	2800
Ограничение скорости	3800
Вес (кг)	3.05
ISO335	
Размеры (ABMA)	2DE
Размеры (мм)	
d	105
d1 □	131
B	43
C	34
r1,2 (мин)	2.5
r3,4 (мин)	2
a	31
Размеры абатмента и галтели (мм)	
да (макс)	117
дБ (мин)	116
Да (мин)	145
Да (макс.)	150
Дб (мин)	153
Са (мин)	7
Сb (мин)	9
ра (макс)	2
rb (макс.)	2
Ценить	
e	0.28
Y	2.1
Эй	1.1

GQZ high quality 33000 Series Single Row Tapered Roller Bearing

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered

roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com