

Single Row Tapered Roller Bearing

33200 Series-33215/Q



BEARING

WUXI GUANGQIANG BEARING TRADE CO.,LTD

Обозначение	33215/Q
Основные размеры (мм)	
d1	75
D	130
B	41
Номинальная грузоподъемность (кН)	
dyc (Cr)	209
stc (Kop)	300
Пу	34
Номинальная скорость (об / мин)	
Рейтинги скорости	3400
Ограничение скорости	4800
Вес (кг)	2.25
ISO335	
Размеры (ABMA)	3EE
Размеры (мм)	
d	75
d1 □	102
B	41
C	31
r1,2 (мин)	2
r3,4 (мин)	1.5
a	32
Размеры абатмента и галтели (мм)	
да (макс)	84
дБ (мин)	84
Да (мин)	111
Да (макс.)	122
Дб (мин)	125
Са (мин)	6
Сb (мин)	10
ра (макс)	2
rb (макс.)	1.5
Ценить	
e	0.43
Y	1.4
Эй	0.8

GQZ high quality 33200 Series Single Row Tapered Roller Bearing

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered

roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com