

Single Row Angular Contact Ball Bearings

7300 Series angular contact ball bearings-7319DT,7319DF,7319DB,7319B 

Номера подшипников

Один ряд	7319B
БД	7319DB
DF	7319DF
DT	7319DT

Основные размеры (мм)

d	95
D	200
B	45
r (мин)	3
r1 (мин)	1.1

Номинальная грузоподъемность (Н)

Cr	167000
Cor	149000

Грузоподъемность (кгс)

Cr	17100
Cor	15200

Ценить

f0	14.6
----	------

Предельная скорость (об / мин)

Смазка	2600
Масло	3600

Расстояние точки действия (мм)

a	84.3
---	------

Размеры абатмента и галтеля

да (мин)	109
Да (макс.)	186
ра (макс)	2.5

Масса

(кг)	5.98
------	------

Значения грузоподъемности (сдвоенный подшипник) (Н)

Cr	272000
Cor	298000

Грузоподъемность (сдвоенный подшипник) (кгс)

Cr	27700
Cor	30500

Предельная скорость (сдвоенный подшипник) (об / мин)

Смазка	2200
Масло	3000

Расстояние до точки действия (сдвоенный подшипник) (a0)

расположение спина к спине	168.7
очная встреча	78.7

Установочные размеры (сдвоенный подшипник)

дБ (мин)	102
Дб (макс.)	193
rb (макс.)	1

GQZ bearings wholesale high quality 7300 Series Single Row Angular Contact Ball Bearings

The dimensional parameters of 7300 series bearings include inner diameter of 10mm, outer diameter of 35mm and thickness of 11mm.

The 7300 series bearings belong to angular contact ball bearings, the specific models and sizes may be different, but the basic size parameters remain the same. For example, NSK 7300 bearings, 7300AC/DF angular contact ball bearings, 7300AC/DT angular contact ball bearings, NSK 7300BDB bearings, NACHI 7300 bearings, and NSK 7300BDT bearings, etc. Despite the differences in models and characteristics, their inner diameters, outer diameters, and thicknesses remain the same, at 10mm, 35mm, and 11mm respectively. These bearings are typically used in applications requiring radial and axial loads with high rotational accuracy and flexibility. In addition, some specific models of the 7300 series bearings have special lubrication properties and seal designs to meet different operating conditions and performance requirements.

7300 Angular Contact Ball Bearing Characteristics

The characteristics of 7300 angular contact ball bearings mainly include high load carrying capacity, high rotational speed, good axial and radial load carrying capacity, as well as being suitable for occasions where high precision is required.

1□High load carrying capacity: 7300 angular contact ball bearings are able to withstand both radial and axial loads, which makes it widely used in the field of industrial machinery. The bearings have a large load carrying capacity and can withstand a large number of radial and axial forces, thus dispersing the load, reducing the stress at a single contact point and prolonging the service life of the bearings.

2□High speed: Due to the design of 7300 angular contact ball bearings, the contact angle between the inner ring and outer ring is designed to be 15° or 25°, which reduces the frictional resistance and lowers the temperature rise, thus increasing the speed of the bearings. This makes it perform well in conditions that require high speed operation, such as machine tool spindles, high-speed motors and other high-precision, high speed mechanical equipment in a wide range of applications.

3□Good axial and radial load carrying capacity: 7300 angular contact ball bearings are designed to allow it to carry axial and radial loads. Although single row angular contact ball bearings can only withstand axial load in one direction, but in the radial load will cause additional axial force, so generally used in pairs to ensure stability and load carrying capacity.

4□Suitable for occasions requiring high precision: 7300 angular contact ball bearings have high precision and repeat positioning accuracy, and are suitable for mechanical equipment requiring high precision. Its manufacturing precision is very high, can use high-strength steel or ceramic material as rolling body, inner and outer ring using high-strength steel, reduce friction and wear, the internal filling of the right amount of grease, to further reduce the friction loss, so as to meet the requirements of high-precision machinery and equipment operation.



Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-
Email:gg@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com