


Four Point Angular Contact Ball Bearing

5200 Series-5201



WUXI GUANGQIANG BEARING TRADE CO.,LTD

Обозначение	5201
Основные размеры (мм)	
d	12
D	32
B	15.9
r (мин)	0.6
Номинальная грузоподъемность (кН)	
Cr	10500
Кор	5800
Грузоподъемность (кгс)	
Cr	1070
Кор	590
Предельная скорость (об / мин)	
Смазка	15000
Масло	20000
Расстояние до точки действия	
a0 (мм)	16.7
Установочные размеры (мм)	
да (мин)	17
Да (макс.)	27
ра (макс)	0.6
Масса	
(кг)	0.06

GQZ high quality 5200 Series Four Point Angular Contact Ball Bearing

Angular contact ball bearings have inner and outer ring raceways that are displaced relative to each other in the direction of the bearing axis. This means that these bearings are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads.

The axial load carrying capacity of angular contact ball bearings increases as the contact angle increases. The contact angle is defined as the angle between the line joining the points of contact of the ball and the raceways in the radial plane, along which the combined load is transmitted from one raceway to another, and a line perpendicular to the bearing axis

The most commonly used designs are:

single row angular contact ball bearings

double row angular contact ball bearings

four-point contact ball bearings

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com