

NU Series

NU2300 cylindrical roller bearing-**NU2322E** 

Обозначение	NU2322E
Основные размеры (мм)	
d	110
D	240
B	80
rs min	3
rs1min	3
Номинальная грузоподъемность (кН)	
Динамический (Cr)	675
Статический (Cor)	880
Ограниченная скорость (об / мин)	
Смазка	2400
Масло	2800
Масса	
(кг)	19.4

GQZ bearings wholesale high quality NU2300 Cylindrical Roller Bearing

The characteristics of NU2300 cylindrical roller bearings mainly include:

Rollers and raceways are in line contact or under repair line contact, which makes NU2300 series bearings have large radial load carrying capacity, very suitable for bearing heavy loads and shock loads.

The coefficient of friction is small, suitable for high-speed operation, and its limiting speed is close to that of deep groove ball bearings, which makes NU2300 series bearings perform well in occasions requiring high-speed operation.

N type and NU type can be moved axially, can adapt to changes in the relative position of the shaft and the shell caused by thermal expansion or mounting errors, and can be used as a free end support.

Higher processing requirements for the shaft or seat hole, bearing installation of the outer ring axis of the relative skew should be strictly controlled, so as not to cause contact stress concentration.

Inner or outer ring can be separated, easy to install and dismantle.



