

Single Row Tapered Roller Bearing

30200 Series-30220J2



WUXI GUANGQIANG BEARING TRADE CO.,LTD

Обозначение	30220J2
Основные размеры (мм)	
d1	100
D	180
B	37
Номинальная грузоподъемность (кН)	
dyc (Cr)	246
stc (Kop)	320
Пу	36
Номинальная скорость (об / мин)	
Рейтинги скорости	2800
Ограничение скорости	3600
Вес (кг)	3.65
ISO335	
Размеры (ABMA)	3FB
Размеры (мм)	
d	100
d1 □	133
B	34
C	29
r1,2 (мин)	3
r3,4 (мин)	2.5
a	35
Размеры абатмента и галтели (мм)	
да (макс)	116
дБ (мин)	112
Да (мин)	157
Да (макс.)	168
Дб (мин)	168
Са (мин)	5
Сb (мин)	8
ра (макс)	2.5
rb (макс.)	2
Ценить	
e	0.43
Y	1.4
Эй	0.8

GQZ high quality 30200 Series Single Row Tapered Roller Bearing

Tapered roller bearings have tapered inner and outer raceways and rollers to handle simultaneous radial and thrust loads. Their axial load carrying capacity is directly related to the contact angle of the rollers and raceway shaft.

They are available in single-row, double-row, and four-row designs. The individual parts of tapered roller bearings are commonly sold separately as cups and cones. Cones contain the roller assembly

and inner ring while cups include the outer ring. Full assembly units contain both the cup and cone. As separable bearings, different designs and sizes are available to accommodate a variety of applications.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com