

Insert Bearings

UY Series insert bearings-



Model

1 UY 211 2S

2 UY 211 2S.SH

Размеры (мм)

d 55

D 100

B 48.4

C 25

s 12.5

d₁ 69.1B₁ 32.5d₂ 76.2B₂ 20.6

E 7

Gs M10×1

sw 5

r1.2 1

r3.4 2

Capacity (kN)

C 43.6

C0 29

Πγ 1.25

Mass

(кг) 0.98

UY Series Single Eccentric Lock Insert Bearing UY205 UY206 UY207 One-Side Extended Inner Spherical Bearing SA AEL Interchange

UY Series Insert Bearings Technical Parameter

Parameter Item	Standard Specification
Full Model Range	UY201 ~ UY210 Metric; UY204-12 ~ UY208-24 Inch Bore
Bearing Type	Single Row Deep Groove Outer Spherical Insert Bearing, Single Eccentric Lock Collar, One-Side Extended Wide Inner Ring

UY-Series-insert-bearings

Parameter Item	Standard Specification
Core Structure	Spherical outer ring (self-aligning $\pm 2^\circ$), inner ring extended on one end, single eccentric locking collar, double-lip NBR composite seal with metal slinger
Raw Material	Inner/Outer Ring: Vacuum degassed GCr15 chrome steel; G10 precision steel ball; stamped steel cage
Locking Mechanism	Single eccentric collar mounted on extended inner ring, tight lock for unidirectional rotation, anti-slip under medium vibration
Seal Option	Standard SL double-lip dust/mud seal; TJ triple-lip heavy-duty seal customizable for harsh farm sites
Internal Clearance	CN standard clearance; C3 extra clearance for high-speed medium vibration equipment
Precision Grade	P0 industrial standard; P6 high precision for food processing equipment
Load Capacity	Medium heavy radial load, light bidirectional axial load
Limiting Rotation Speed	Grease lubrication: 3600 ~ 5100 r/min (size dependent)
Operating Temperature	-30°C ~ +120°C
Interchangeability	Fully interchangeable with FYH SA, NTN AEL, SNR ES series eccentric lock insert bearings
Matching Housings	UCP pillow block, UCF 4-bolt flange, UCFL 2-bolt flange, UCT take-up housing
Certificates	ISO9001, RoHS
HS Code	8482102000
Core Features	One-side extended wide inner ring for eccentric collar installation; single eccentric collar provides strong anti-slip force for single-direction rotation; spherical outer ring compensates mounting misalignment; double anti-dust seal adapts to farm muddy environment; pre-filled long-life grease with external grease nipple for re-lubrication; simple structure with cost advantage.

UY Series Insert Bearings Product Features

- One-side extended wide inner ring design, matched with single eccentric locking collar, generates strong self-locking friction during single-direction rotation, effectively preventing inner ring slipping under medium farm vibration.
- Simple eccentric locking structure with fewer accessories, lower production cost than double eccentric UH or concentric UE series, excellent cost performance for single rotation equipment.
- Spherical outer ring self-aligning design allows $\pm 2^\circ$ angular misalignment compensation, eliminates abnormal noise and premature raceway spalling caused by housing assembly deviation.

- Standard SL double composite lip seal with outer metal slinger, multi-stage barrier against mud, crop dust and water splashing, suitable for medium-harsh farm working conditions.

FAQ

Q1: Can you provide custom bearings?

Yes, we support OEM and custom production based on your drawings, samples, or technical requirements.

Q2: What is the delivery time?

Standard models: 7-15 working days. Custom products: depending on specifications and order quantity.

Q3: Looking for a reliable agricultural bearing supplier?

Send your inquiry to get:

Fast quotation within 24 hours

Technical support from experienced engineers

Custom solution suggestions for your application

Competitive factory-direct pricing

Click Send Inquiry or contact us now to discuss your bearing requirements.

Wuxi Guangqiang Bearing Trade Co.,Ltd-Tel:86-510-82601571-
Email:gq@gqbearing.com,shary@gqbearing.com-http://www.bearing-asia.com